

Performance Ultra-stable
Advanced Functions
Convenient Operation

This series flowmeter is clearviewing type with SS valves to adjust the flowrate in a large measuring range. It is featured in a beautiful look and easy installation.

LZM-ZT

Technical Parameters of LZM-ZT series TFlow Meter

Model	Measure Range			Screw thread	Accuracy
	GPM (Liquid)	LPM (Liquid)	Nm ³ /h (Gas)		
LZM-15ZAT		15-150LPH	0.1-1 0.3-3 0.4-4	1/2"	±4%
LZM-15ZT		10-100LPH	0.6-6 1-10 1.6-16 2.5-25 4-40		
		16-160LPH			
		25-250LPH			
	0.1-1	0.5-4			
	0.2-2	1-7			
LZM-25ZT	0.3-3	1-11	20-100 50-2		
	0.5-5	2-18			
	2-10	10-35			
	4-14	15-50			
	6-20	20-70			
	10-35	30-130			
	10-40	30-150			
	15-45	50-170			



The material code of the parts of LZM-series Flow Meter

Valve	Fitting	Float	O-ring
1 SS 2 Brass	1 ABS 2 PP 3 PVC 4 Brass 5 Brass chromeplate 6 SS	✓ 1 SS	✓ 1 Silicon rubber 2 Fluorin rubber

For Order: please specify the model, specification and code.

Model Regulating Valve Measuring Range Material of the fitting Material of the O-ring

LZM- T

The outline size of LZM-ZT series Flow Meter

Model	Size (mm)							
	A	B	C	D	E	F	G	H
LZM-15ZA	157	32	150	35	25	60	25	110
LZM-15Z	175	32	168	35	25	76	25	127
LZM-25Z	234	45	226	46	33	100	37	160

