

STAINLESS STEEL ELECTRONIC THERMOMETERS



Long working autonomy, up to 2-4 years without replacing the battery.
 IP 65 protection grade (for electronic parts).
 Completely made of stainless steel.
 Customized frontal part.
 N. 4 measuring ranges, from -50°C to $+150^{\circ}\text{C}$ in order to cover a wide range of applications.
 Display digits h. 13mm.
 Possibility of immediate substitution of traditional analogical models.




TAX 10

Axial probe: suitable for tanks and for local control of the process.

DATI TECNICI | TECHNICAL DATA

Standard measuring ranges	$-40^{\circ}\text{C} \div 50^{\circ}\text{C}$ $-20^{\circ}\text{C} \div 70^{\circ}\text{C}$ $-10^{\circ}\text{C} \div 110^{\circ}\text{C}$ on request $-50^{\circ}\text{C} \div 150^{\circ}\text{C}$ / $-50^{\circ}\text{C} \div 300^{\circ}\text{C}$
Resolution	$0,1^{\circ}\text{C}$, (Max. $0,2^{\circ}\text{C}$) * 1°C
Accuracy	Better $\pm 0,4^{\circ}\text{C}$ than
Operating temperature	$-5 \div 50^{\circ}\text{C}$
Sampling	1 reading every 10 seconds (optional: 1 reading/second)
Power supply	1 x LR6 AA alkaline battery 1.5V
Battery lifetime	Minimum 2 years (samp. 1 sec.) minimum 4 years (samp. 10 sec.)

DIMENSIONS



1/2