

ORDER DIAGRAM FLU/P

FLU/P 4 C 5-15 2 B S A L3000

CONNECTION			FLOWRATE
1	WATER	1/4" BSP	0,1...7
2	WATER	3/8" BSP	0,5...12
3	WATER	1/2" BSP	1...20
4	WATER	3/4" BSP	5...24
5	WATER	3/4" BSP	5...36
6	WATER	1" BSP	10...42
7	WATER	1"1/4 BSP	20...95
8	WATER	1"1/2 BSP	30...120
9	OIL (O)	1/4" BSP	0,1...6
10	OIL (O)	3/8" BSP	0,5...10
11	OIL (O)	1/2" BSP	1...16
12	OIL (O)	3/4" BSP	5...20
13	OIL (O)	3/4" BSP	5...30
14	OIL (O)	1" BSP	10...35
15	OIL (O)	1"1/4 BSP	20...80
16	OIL (O)	1"1/2 BSP	30...100

CABLE LENGTH SENSOR S2		
S	STANDARD	1500 mm
L	A RICHIESTAmm

TYPE OF CONTACT SENSOR S2	
A	SPST CH IN ABSENCE
B	SPST CH IN PRESENCE
C	SPDT
D	SPST CH IN ABSENCE GREEN LED
E	SPST CH IN ABSENCE RED LED
F	SPST CH IN PRESENCE GREEN LED
G	SPST CH IN PRESENCE RED LED

FLOWRATE	
S	STANDARD
C	CUSTOM (MIN-MAX)

TYPE OF CONTACT SENSOR S1	
A	SPST CH IN ABSENCE
B	SPST CH IN PRESENCE
C	SPDT
D	SPST CH IN ABSENCE GREEN LED
E	SPST CH IN ABSENCE RED LED
F	SPST CH IN PRESENCE GREEN LED
G	SPST CH IN PRESENCE RED LED

SENSORS	
1	1 SENSOR
2	2 SENSOR

CABLE LENGTH SENSOR S1		
S	STANDARD	1500 mm
L	A RICHIESTAmm